DATA SHEET

VARIAIR SV 201/2
SIDE CHANNEL VACUUM PUMPS

double stage, air-cooled
frequency inverter


MAKE IT BECKER.



figure VARIAIR SV 300

VARIAIR UNIT


BECKER



1 Vacuum connection (G2)
2 Pressure connection (G2)
3 Rubber buffer position (optional)
4 Optional with shorter silencers
* Device dimensions without pedestal (optional) under the silencer
▪ Dimensions in mm [inch]

Suction air rate	Vacuum relative	Frequency	Emission sound pressure level[1)]	Weight		
m^3/h max.	mbar max.	Hz	dB(A) @ -290 mbar (67 Hz)	kg	Frequency inverter VAU4/4	A max.
175	-420	10–100	73.5	32	4.0 kW 400–480 V ±10% 50/60 Hz	16

[1)] According to DIN EN ISO 11203, accuracy class of measurement: class 2, extended measurement uncertainty: 3 dB
1 m [39.4 inch] distance, at medium load, both connection sides piped



Reference data (atmosphere): 1000 mbar (100 kPa), 20°C (68°F)
Tolerance: ±10%
Max. ambient temperature: -10°C ... 40°C (14°F ... 104°F)

Right of modification reserved 2022-06-01

MAKE IT BECKER.