
DATA SHEET

VARIAIR SV 300/1

SIDE CHANNEL BLOWERS


single stage, air-cooled, gas-tight
VARIAIR frequency inverter

MAKE IT BECKER.



VARIAIR UNIT


BECKER



1 Vacuum connection DN 63 ISO-K (DIN 28404)
2 Pressure connection DN 63 ISO-K (DIN 28404)
3 Rubber buffer position (optional)
* Device dimensions without pedestal (optional) under the silencer
▪ Dimensions in inch

Flow [1]	Pressure ratio [1]	Frequency	Emission sound pressure level [2]	Weight	Frequency inverter [3]
CFM max.	p/p max.	Hz	dB(A) 1.25 p/p (67 Hz)	lbs	
352.8	1.375	10–100	76	143.3	400–480 V ±10% 50/60 Hz

[1] Measured for argon at reference data (atmosphere): 0 PSIG, 68°F; tolerance: ±10%
Leakage rate <1x10^{-5} mbar l/s (<1x10^{-6} Pa m^3/s) measured with a helium leak detector, integral for the complete unit
[2] According to DIN EN ISO 11203, accuracy class of measurement: class 2, extended measurement uncertainty: 3 dB
39.4 inch distance, at medium load, both connection sides piped, suction side unloaded
[3] The frequency inverter is designed for a specific maximum motor power. (See inverter instructions for details.)
The motor is selected on the basis of the required motor shaft power. Therefore, the installed motor power may be less than the maximum power supported by the inverter.



Reference data (atmosphere): 0 PSIG, 68°F
Tolerance: ±10%
Measured for argon (deviating characteristics for other inert gases)
Ambient temperature: ≤ 113°F
Inlet pressure: ≤ 0.725 PSIG

Right of modification reserved 2024-10-11

MAKE IT BECKER.

www.beckerpumps.com
www.becker-international.com

BECKER